


Installation Instruction :


- -Please read this manual carefully before installation and operate accordingly.
- -Strict compliance to this manual can make sure the stable performance and safety, please keep this manual properly.
- -The installation must be done by professional qualified electrician.

-Modification and violent usage to the device in any circumstances are not allowed. Any modification or amendment will affact the performance safety and becom dangerous. LiteMatrix will not take any responsibility due to this.




WARNING : IN DOOR USE ONLY !





ATTENTION : PLEASE PUT THIS LAMP ON HORIZONTAL FLAT GROUND WHEN USING. PLEASE DO NOT PUT HEAVY STAFF ON THE LAMP OR BEING COVERED BY INSULATION MATERIALS. _____



Form 1- Specs.

Model No.	Weight (kg)	Power Supply Type	Housing Color
7007101			
7007102	23KG	Integrated Driver	Black/White
7007103			

-EN60598 Regulation : The lateral distance between the surface of the luminaire and any parts of the building must be no less than 50mm

- The tilt angle is controlled within $\pm 6^{\circ}$ when lamp is standing.

- Installation and usage environment : Ta=25°C.

SHENZHEN LITEMATRIX LIGHTING CO., LTD

Phone: +86 755 2689 5498

Block2, Hongtu Industrial Park, Hezhou, Xixiang, Bao'an Fax: District, Shenzhen, China. website: www.litematrixlighting.com F-mail[.]

+86 755 2686 0743

sales@litematrix net

LiteMatrix reserves its right to modify or updated the specs without prior notice. 2016.12




Instruction Manual Patronus Free Standing 7007101

Installation- Integrated Driver Version


1. Please make sure the power switched off before installation, put on gloves and operate in dry a dry indoor environment.

2. Take out the lamp pole(A), and lamp base(B), insert the lamp pole(A) into the base(B) in the direction as picture below shown. Take out the big wrench(D) and the cylindrica head screws(C) from the accessories bag; tighten up the screws as shown in picture below.






3. Take out the lamp head (E), insert it into the lamp pole(A); take out the small wrench(F) and the Countersunk head screws(G) from the accessories bag; tighten up the screws as shown in picture below.




4. Please make sure the lamp is completely well installed

before connecting the power cable.



Touching Control Panel



Switch Description :

1. Connect the main power, the green power indicator light is on,

which means the lamp is power on. Single touch the Power Switch, the lamp is On/Off.

2. Single touch the Up Light Control mark, up light will be Off/On. 3. Single touch the Down Light Control mark, down light will be Off/On.

4. Press the Up Light Control/Down Light Control mark and hold on, the Up/ Down light becomes brighter and no change until achieve the max brightness; Remove the finger, press again and hold, the brightness will decrease till the minimum level.

5. The lamp will memorize the last set-up of brightness when re-start.

Intelligent Sensor Mode

2 智能模式开关

Sensor Description :

1. Intelligent Sensor Mode can be switch Off/On and only working when it's On.

2. Human presence sensor can detect the movement in an area of

1 meter distance. Sensor delay time is 40 minutes and beyond that, the

lamp will switch off automatically and switch on with last set-up when

another movement appears.

3. Constant Lux Managing system enable the lamp adjust the light output automatically according to the surrounding lux level and

maintain the same lux level on the desk all the time.

SHENZHEN LITEMATRIX LIGHTING CO., LTD

Block2, Hongtu Industrial Park, Hezhou, Xixiang, Bao'an District, Shenzhen, China website: www.litematrixlighting.com

Phone: +86 755 2689 5498

+86 755 2686 0743

Fax:

sales@litematrix net F-mail

LiteMatrix reserves its right to modify or updated the specs without prior notice. 2016.12

Cleaning

Please clean the dirties on the lamp surface regularly. Please cut off the power first and use soft cloth only. For intractable dirt, please use wet soft cloth with soap or neutral detergent to wipe clean.



According to WEEE regulation , the lighting fixture is not allowed to disposal with other household electrical appliances, must be properly deal with or recycled.