

Product description

System X is a perfect integrated lighting system. Thanks to the advanced lighting technology, X series can achieve ultra compact structure and size, with a recessed, surface or suspended installation, that can perfectly integrate into the building and has minimum impact on architecture. Minimalist extruded aluminum profile, available to do flexible continuous connection into any lengths or shapes. Versatile LED lighting Modules are provided for free combination with tool-free installation for all kinds of applications: General Lighting, Accent Lighting, Wallwashing. X not only means inclusiveness, but also the infinity extensions.

Product features

- Compact body made of aluminum
- Rotates through 360° and tilt through 0-90°
- Easy to be fixed on the track by magnetic force
- Deep inside hidden light source and unique ToD optic system helps to create high visual comfort
- High power LED
- On-off/DALI/Wireless/Potentiometer dimming available
- DALI versions occupy 1 address
Wireless versions occupy 1 address


- Housing – matt black/white
Reflector – specular silver/black

Technical data

Input	DC24V
Power consumption	8.5W
CRI	>90
CCT	3000K
Beam angle	40°
Chromaticity tolerance	<3 SDCM
Rated lifetime	50000H (Ta 25°C)
Dimming method	On-off or DALI/Wireless or Potentiometer
Dimming range	On-off or 0-100% or 3%-100%
Mechanical adjustment	Horizontal: 0-360° ; Vertical: 0-90°

Luminous intensity distribution curve

LED 7W 530lm 3000K



H(m)	D(m)	E(lx)
1.0	0.71	930
2.0	1.42	233
3.0	2.14	103
4.0	2.85	58
5.0	3.56	37


配件信息



M9102201.001
Reflector
Specular silver




M9102201.002
Reflector
Specular black



M9102201.003
Mechanical hook



M9103501.001
Cylindrical screen
(Snoot)



M9103507.002
Honeycomb
louvre